

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problems Mailbox.**

**THIS PAGE BLANK (USPTO)**

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau




(43) International Publication Date  
26 July 2001 (26.07.2001)

PCT

(10) International Publication Number  
**WO 01/54126 A1**

- (51) International Patent Classification<sup>7</sup>: **G11B 20/12**, 27/10, 27/30, 27/32, H04N 7/52, 7/24
- (21) International Application Number: **PCT/EP00/11335**
- (22) International Filing Date:  
16 November 2000 (16.11.2000)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
00100836.6 17 January 2000 (17.01.2000) EP
- (71) Applicant (for all designated States except US):  
**DEUTSCHE THOMSON-BRANDT GMBH [DE/DE]**;  
Hermann-Schwer-Strasse 3, 78048 Villingen-Schwenningen (DE).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **WINTER, Marco [DE/DE]**; Böhmerstrasse 17, 30173 Hannover (DE).  
**SCHILLER, Harald [DE/DE]**; Apfelgarten 11, 30539 Hannover (DE).
- (74) Agent: **RITTNER, Karsten**; Deutsche Thomson-Brandt GmbH, European Patent Operations, Karl-Wiechert-Allee 74, 30625 Hannover (DE).
- (81) Designated States (*national*): AE, AG, AL, AU, BA, BB, BG, BR, CA, CN, CR, CU, CZ, DM, DZ, EE, GE, GR, HU, ID, IL, IN, IS, JP, KP, KR, LC, LK, LR, LV, MA, MG, MK, MN, MX, NO, NZ, PL, RO, SG, SI, SK, TR, TT, UA, US, UZ, VN, YU, ZA.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: METHOD FOR RECORDING OR PLAYBACK OF LOW BITRATE DATA STREAMS



(57) Abstract: DVD Stream Recording shall be used for realtime recording and playback of given packetized bitstreams. The data of the bitstream are organized into Stream Object Units, which in turn consists of stream packs (O\_S\_P) with a stream pack header (P\_H) followed by a stream packet (S\_PES\_P), wherein a stream packet (S\_PES\_P) contains further header data (PES\_H, S\_ID, A\_H) and an Application Packet Area (A\_P\_A), which is filled with a sequence of Application Packets each prefixed by an Application Time Stamp (ATS). In case of very low bitrate stream recording empty packets are recorded, which are marked as stuffing packets. This ensures that every Stream Object Unit - even in areas where stuffing is performed - contains at least one Application Time Stamp value.

WO 01/54126 A1

## Method for recording or playback of low bitrate data streams

The invention relates to a method for recording or playback of low bitrate data streams to be recorded or being recorded on a storage medium, e.g. an optical disc.

### Background

10

Like the CD also its successor, the DVD (digital versatile disc), can be used for various technical purposes. Therefore, different DVD specifications have been defined, like DVD-Video, DVD-Audio and DVD-ROM for the mass distribution of prerecorded motion pictures, music and software programs, respectively. For recording on DVD discs DVD-RAM and DVD+RW serve for general read-and-write applications in the PC or consumer electronics area, while DVD-R is used for write-once recordable media and DVD-RW is a rewritable version of DVD-R. Still under development is a specification for rewritable/re-recordable DVD discs called DVD Stream Recording, abbreviated DVD-SR. DVD-SR shall be used for realtime recording and playback of given packetized bitstreams, wherein the disc in which data are recorded shall comply with any recordable or rewritable or re-recordable media and file system format prescribed in other DVD specifications.

In general, various packetizing formats of bitstreams are used for different applications depending on the system parameters. The MPEG-2 systems standard as defined in ISO/IEC 13818-1 specifies two different formats, the so-called program stream and transport stream. While the transport stream is used for applications with a relatively high error rate, e.g. the transmission of a DVB data stream via satellite, the program stream is used in

the case of low error rates like data storage.

The structure of DVD-SR recorded bitstreams shall comply basically with the program stream as defined in ISO/IEC 13818-1. The data of the bitstream are recorded as Stream Objects (SOBs), wherein SOBs are organized into Stream Object Units (SOBUs) of a constant size of 64 kbyte. Each SOBU in turn consists of a constant number of so-called stream packs consisting of a pack header followed by a stream packet. A stream packet contains further header data and Application Packet (AP\_PKT) data. To each AP\_PKT an Application Timestamp (ATS) is assigned. This timestamp enables proper Application Packet delivery during playback.

The time interval captured by a SOBU is not defined but flexible which means that the playback time of a SOBU can vary largely depending on the momentary bitrate of the recorded stream. Therefore, a Mapping List (MAPL) is used for pointing to that SOBU where the desired AP\_PKT can be found. Relative time stamps "Incremental APAT" (IAPAT) are assigned to each of the SOBUs corresponding to the time duration of the recorded signal in the respective SOBU. The IAPAT time stamps are derived from times stamps called Application Packet Arrival Time (APAT) which are assigned to incoming Application Packets during recording based on the local reference clock of the DVD-SR.

A limited resolution of 12 bits is used for the IAPAT values, because the MAPL has to be kept in the memory of the streamer device, e.g. a RAM. The maximum IAPAT value corresponds to an upper limit of a SOBU time duration of about 23,3 seconds. This limits the minimum bitrate of a data stream to be recorded to a value of about 5.5 kbit per second.

### Invention

It is one object of the invention to disclose a method for recording or playback of packetized bitstreams which is not restricted to the above mentioned minimum bitrate and therefore allows also the recording and playback of very low bitrate data streams. This object is achieved by the method disclosed in claim 1.

10

The invention is based on the recognition of the fact that a DVD-SR should also be applicable for certain applications where very low bitrates occur temporary or even permanently. However, in case of very low bitrate stream recording there could be less than one application packet and therefore less than one ATS per Stream Object Unit. Therefore, according to the current draft of the DVD-SR specification the proper functioning of the Mapping List data retrieval is not guaranteed.

20

According to the invention in the case of very low bitrates empty packets are recorded, which are marked as stuffing packets.

25 The use of these stuffing packets replacing application packets ensures that every Stream Object Unit - even in areas where stuffing is performed - contains at least one Application Time Stamp value. This allows also the recording and playback at very low bitrates, e.g. 100  
30 bit/second.

### Drawings

35 Embodiments of the invention are described with reference to the accompanying drawing, which shows in:

Fig. 1 the structure of stream packs containing parts of Stuffing Packets.

## 5 Exemplary embodiments

Abbreviations used for describing the drawing are explained in the following:

### 10 SOB (Stream Object):

1) one take (after editing an origin SOB may be splitted into more than one SOB)

2) consists of MAPL\_ENT\_Ns SOBUs (MAPL\_ENT\_Ns >= 1; MAPL\_ENT\_Ns is located in the SOBI of this SOB, i.e. in  
15 the IFO file)

3) the stream itself consists of SOBUs (located in the SRO file)

4) information (location, recording time, start and end time et cetera) about the stream is stored in the SOBIs

20 (located in the IFO file) --> SOBI = SOB Information

### SOBU (SOB Unit):

1) is stored in the SRO file

2) each SOBU consists of 65536 bytes = 32 sectors = 32

25 Stream packs = 32 stream packets

3) a stream consists of contiguous SOBUs

### AP\_PKT (Application Packet):

1) is stored in the AP\_PKT area of a Stream packet (SRO  
30 file)

2) an AP\_PKT contains the actual payload of the stream

2) an ATS (Application Time Stamp) is in front of each AP\_PKT

3) 1 byte =< AP\_PKT size =< 64574 bytes

35 4) an AP\_PKT starting in AP\_PKT area of sector X may end in the AP\_PKT area of sector X+Y, with 0=<Y=<31

5) the data of an AP\_PKT may even cover a SOBU boundary

APAT (AP\_PKT Arrival Time):

- 1) 48 bit time stamp
- 5 2) absolute time stamp
- 3) most exact time stamp of the DVD SR spec
- 4) all other time stamps are sub-sets of an APAT
- 5) the 9 LSB of an APAT describes the 27MHz part of the APAT
- 10 6) the (remaining) 39 MSB of an APAT describes the 90kHz part of the APAT

IAPAT (Incremental AP\_PKT Arrival Time):

- 1) element of the MAPL (Mapping List --> see below)
- 15 2) relative time stamp (contains the duration of a SOBU) -  
-> it's the only relative time stamp of the spec
- 3) range:  $1..2^{12-2}$  (i.e. 5.6ms ... 23.3s) --> 12 bit value
- 4) unit:  $IAPAT * 512 / 90000Hz$
- 20 5)  $IAPAT\#n$  is  
the up-rounded first occuring ATS of  $SOBU\#n+1$   
minus  
the up-rounded first occuring ATS of  $SOBU\#n$ .  
Up-rounding means ceiling( $ATS/2^{18}$ ).
- 25 6) the bits 18 to 29 of an APAT correspond to the 12 bits of an IAPAT

MAPL (Mapping List):

- 1) is stored in the IFO file
- 30 2) each SOBI contains one MAPL
- 3) a MAPL consists of  $MAPL\_ENT\_Ns\_IAPAT$  values
- 4)  $MAPL\_ENT\_Ns$  is equal to the number of SOBUs used by this SOB
- 5) MAPL and  $MAPL\_ENT\_Ns$  are located in the SOBI

6) is used to locate an AP\_PKT inside the stream (i.e. to locate sector and the start byte of the AP\_PKT inside this sector) via a timestamp (APAT)

5 SUM\_IAPAT (summation of the IAPATs of an MAPL):

1) is not stored anywhere, i.e. must be calculated by summation of the MAPL entries (IAPATs)

2) is used to find the coarse location of the start of an AP\_PKT inside the stream via the timestamp of this AP\_PKT

10 3) if X is the timestamp of an AP\_PKT we are searching for and

X is between SUM\_IAPAT(k) and SUM\_IAPAT(k+1), then the searched AP\_PKT starts either in SOBU#k or in SOBU#k+1 --> the result of the search is 2 SOBUs exact

15 4) after this coarse search the exact location of the AP\_PKT must be found via a direct search inside the stream

5) the bits 18 to 47 of an APAT (i.e. the 30 MSB of an APAT) correspond with SUM\_IAPAT

20 ATS (Application Time Stamp):

1) 32 bit time stamp, located in the stream (SRO file)

2) absolute time stamp

3) range:  $1..2^{32}-1$  ( $1/27\text{MHz} \dots 93.2\text{s}$ ) --> i.g. wrap  
arounds occur inside the stream. I.e. the range of an ATS  
25 is too small to be an unambiguous pointer into one whole SOB. Only a complete APAT value is able to be an unambiguous timestamp for a whole SOB.

4) unit of the 23 MSB: 1/90kHz

5) unit of the (remaining) 9 LSB: 1/27MHz

30 6) exact one ATS is at the front of each AP\_PKT

7) exact one ATS is at the front of each Stuffing packet

8) the bits 0 to 31 of an APAT correspond to the 32 bits of an ATS

9) the bits 18 to 29 of an ATS have the range of the 12

35 bits of an IAPAT --> of course, IAPAT is relative and ATS is absolute! Therefore, both are not really compareable.

As shown in Figure 1a, a stream pack O\_S\_P of 2048 byte consists of a stream pack header P\_H of 14 byte and a  
5 stream PES packet S\_PES\_P of 2034 byte. The stream PES packet S\_PES\_P consists of a PES header PES\_H of 6 byte, identification data S\_ID of 1 byte designating the subsequent payload as Stream Recording Data and a stream data area S\_D\_A of 2027 byte. The Stream Data Area S\_D\_A inside  
10 a stream packet consists of an Application Header A\_H of 9 byte and an Application Packet Area A\_P\_A of 2018 byte. For normal bitrates the Application Packet Area A\_P\_A is filled with a sequence of AP\_PKTs, each prefixed by an Application Time Stamp ATS. The ATS consists of a 32-bit  
15 value and is divided into two parts, namely a base part and an extension part.

In cases of very low bitrate stream recording, stuffing is performed in order to guarantee the proper functioning of  
20 the Mapping List data retrieval. For this purpose, a Stuffing Packet is defined as a conceptual unit. The purpose of the stuffing packet is to ensure that every SOBU - even in areas of stuffing - contains at least one Application Time Stamp ATS value. As shown in figure 1 b, in the  
25 stream pack containing the start of the stuffing packet the Application Packet Area A\_P\_A consist of one ATS of 4 Bytes followed by an area Z1 of stuffing bytes. The subsequent stream packs contain the rest of the stuffing packet. An Application Packet Area A\_P\_A consisting only  
30 of stuffing bytes Z2 is schematically shown in figure 1 c.

Stuffing Packets shall fulfill the following rules:

Stuffing Packets always start at the start of the Application Packet Area of the stream pack after the stream pack  
35 containing genuine Application Packet data.

Stuffing Packets consist of one ATS of 4 Bytes, followed by as many zero bytes as are needed to fill the Application Data Areas of the remaining packs of the SOBU. Therefore, the total length of a Stuffing Packet is  $(4 + 2014 + (n - 1) * 2018)$  Bytes, where  $0 \leq n < \text{SOBU\_SIZ}$  and  $\text{SOBU\_SIZ}$  is the number of packs in one SOBU.

Although a value of zero for the stuffing bytes may be appropriate for most applications, it is of course also possible to choose other values for filling the Application Data Areas.

The ATS of a Stuffing Packet shall be set as follows:

- in a SOBU where at least one pack contains genuine Application Packet data, the ATS of the Stuffing Packet shall be set to the ATS of the Application Packet preceding the Stuffing Packet;
- in a SOBU where no real Application Packet data are contained, the ATS of the Stuffing Packet shall be set to

$$\text{ATS} = \text{SUM\_IAPAT}(k-1)[(31 - \text{MTU\_SHFT}).0] * 2^{\text{MTU\_SHFT}}$$

where  $\text{SUM\_IAPAT}$  is derived from entries of a Mapping List (MAPL) comprising time stamps assigned to the Stream Object Units and  $\text{MTU\_SHFT}$  is a constant derived from the Stream Object Unit size and the maximum allowable bitrate.

All packs containing Stuffing Packets or parts of Stuffing Packets shall be constructed as follows:

- the System Clock Reference SCR, as specified by the MPEG-2 Systems standard, of the Pack Header shall be calculated according to

$$\text{SCR} = \text{SCR\_previous} + 2048 * 8 \text{bits} / 10.08 \text{Mbps},$$

where SCR\_previous shall denote the SCR of the previous pack of the DVD Streamer specification;

- the PES Packet Header PES\_H and the identification data S\_ID shall be specified same as for all other PES Packets;
- the Application Header shall be specified with AP\_Ns=0, FIRST\_AP\_OFFSET=0, EXTENSION\_HEADER\_INFO=00b, SERVICE\_ID=0, MAX\_BR\_LOG2=0, and SMO\_BS\_LOG2=0, where these parameters are defined in the preliminary DVD streamer specification.

For the upper limit of the mapping list entries, it has been derived that for all Application Packets  $i$  in a SOBU  $k$ , the following upper limit must be kept

$$APAT_i[47..18] < \text{sum\_iapat}(k-1) + (2^{12} - 2),$$

where  $APAT_i$  is the Application Packet Arrival Time of Application Packets  $i$ , i.e. an absolute timestamp having e.g. a 48-bit value format.

In order to guarantee that the limitation of this equation is being kept, the following steps or any equivalent operations can be performed during recording:

- a) Upon filling a SOBU with data, memorize the ATS of the first Application Packet (AP), which starts in the current SOBU.
- b) Continuously check the Streamer system clock TSC, whether it fulfils

$$TSC[47..18] < \text{sum\_iapat}(k-1) + (2^{12} - 2)$$

- c) As soon as this is violated,
  - c.1) Terminate the current recording sector, using an AP\_PKT\_Ns value which might be smaller than techni-

cally possible, wherein AP\_PKT\_Ns is the number of AP\_PKTs starting in this Stream Pack.

c.2) Terminate the current SOBU by filling the remainder of the SOBU - if necessary - with a Stuffing Packet as described above; write current SOBU data to disc.

c.3) Create a mapping list entry  $IAPAT(k) = 2^{12} - 2$

c.4) Increment k by 1.

c.5) Start the recording of SOBU#k and open its first sector for recording.

c.6) If an AP\_PKT arrives at  $TSC[47..0] = SUM\_IAPAT(k-1) * 2^{18}$ , then proceed to step at a)

c.7) Record SOBU#k as a SOBU containing only a Stuffing packet ( $ATS = SUM\_IAPAT(k-1)[13..0] * 2^{18}$ ).

c.8) If no AP\_PKT arrives during  $TSC[47..18] < SUM\_IAPAT(k-1) + (2^{12} - 2)$ , then proceed to step c.3)

c.9) AP\_PKT is the first AP\_PKT of SOBU#k+1.

c.10) Set  $IAPAT(k)$

c.11) Increment k by 1.

c.12) Proceed to step a)

The application packets may contain any type of data, e.g. video or audio or additional data like service information. The data rate to be handled in the streamer may therefore range up to e.g. an 80 Mbit/s peak data rate value for detailed complexly moving scenes of video signals.

The invention can be used in any apparatus for recording and playback of packetized bitrate data streams, e.g. a so-called DVD streamer. Furthermore, the invention can be used for arbitrary storage media for recording and playback of packetized bitrate streams, especially for DVD discs.

Claims

1. Method for recording or playback of low bitrate data streams, wherein packets of the data stream are recorded  
5 in data blocks of constant size and time stamps are used for addressing of the data blocks, the time stamps corresponding to the time duration necessary for a total filling of a data block at the used bitrate, and wherein a maximum time duration is defined corresponding to the total filling of a data block at a minimum bitrate, **characterised** by that in the case of bitrates below the minimum  
10 bitrate empty packets are recorded, which are marked as stuffing packets.
- 15 2. Method according to claim 1, wherein the recorded data are organized into Stream Object Units consisting of stream packs (O\_S\_P) with a stream pack header (P\_H) followed by a stream packet (S\_PES\_P), wherein a stream packet (S\_PES\_P) contains further header data (PES\_H, S\_ID, A\_H) and an Application Packet Area (A\_P\_A), which  
20 is filled with a sequence of Application Packets prefixed by an Application Time Stamp (ATS), wherein in the stream pack containing the start of the stuffing packet the Application Packet Area (A\_P\_A) consists of an Application  
25 Time Stamp (ATS) followed by stuffing bytes (Z1) and the subsequent stream packs contain the rest (Z2) of the stuffing packet.
3. Method according to claim 2, wherein a Stuffing  
30 Packet starts at the start of the Application Packet Area (A\_P\_A) of the stream pack (O\_S\_P) after the stream pack containing genuine Application Packet data.
4. Method according to claim 2 or 3, wherein Stuffing  
35 Packets consist of an Application Time Stamp (ATS), followed by as many zero bytes as are needed to fill the Ap-

plication Data Areas of the remaining packs of the Stream Object Unit.

5. Method according to any of claims 2 to 4, wherein the Application Time Stamp (ATS) of a Stuffing Packet is set as follows:

- in a Stream Object Unit where at least one pack contains genuine Application Packet data, the Application Time Stamp (ATS) of the Stuffing Packet is set to the Application Time Stamp (ATS) of the Application Packet preceding the Stuffing Packet;
- in a Stream Object Unit where no real Application Packet data are contained, the Application Time Stamp (ATS) of the Stuffing Packet is set to

15

$$ATS = SUM\_IAPAT(k-1)[(31-MTU\_SHFT).0]*2^{MTU\_SHFT}$$

where SUM\_IAPAT is derived from entries of a Mapping List (MAPL) comprising time stamps assigned to the Stream Object Units and MTU\_SHFT is a constant derived from the Stream Object Unit size and the maximum allowable bitrate and k is the number of this Stream Object Unit.

25 6. Apparatus for recording or playback of low bitrate data streams according to any of claims 1 to 5.

7. Storage medium for recording or playback of low bitrate data streams according to any of claims 1 to 5.

30




Fig. 1

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 00/11335

## A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 G11B20/12 G11B27/10 G11B27/30 G11B27/32 H04N7/52  
H04N7/24

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 G11B H04N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ, IBM-TDB, INSPEC

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP 0 737 975 A (TOKYO SHIBAURA ELECTRIC CO) 16 October 1996 (1996-10-16) column 22, line 30 -column 28, line 7 column 34, line 58 -column 35, line 21 figures 32-36	1-7
Y,P	EP 0 986 062 A (THOMSON BRANDT GMBH) 15 March 2000 (2000-03-15) abstract page 6, line 7 -page 9, line 40 figures 4,6	1-7
Y,P	EP 1 021 048 A (TOKYO SHIBAURA ELECTRIC CO) 19 July 2000 (2000-07-19) page 5, line 15 - line 55 page 19, line 47 -page 21, line 24 figures 3,38,39	1-4,6,7
	-/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*&\* document member of the same patent family

Date of the actual completion of the international search

26 February 2001

Date of mailing of the international search report

06/03/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040. Tx. 31 651 epo nl.  
Fax: (+31-70) 340-3016

Authorized officer

Schiwy-Rausch, G

# INTERNATIONAL SEARCH REPORT

International Application No

PCT/EP 00/11335

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y,P	<p>EP 0 986 248 A (THOMSON BRANDT GMBH)  15 March 2000 (2000-03-15)  page 2, line 37 -page 3, line 12  page 4, line 1 - line 14  page 6, line 34 -page 9, line 31  figure 3</p>	1-4,6,7
A	<p>EP 0 967 603 A (TOKYO SHIBAURA ELECTRIC  CO) 29 December 1999 (1999-12-29)  column 7, line 38 -column 8, line 14  column 9, line 6 - line 54  column 19, line 25 - line 41  column 24, line 18 - line 31  column 26, line 36 - line 53  figures 5,20,27</p>	1-4,6,7

# INTERNATIONAL SEARCH REPORT

Inte. .onal Application No

PCT/EP 00/11335

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0737975 A	16-10-1996	AT 182026 T	15-07-1999
		CA 2173812 A	12-10-1996
		CN 1137147 A	04-12-1996
		DE 69603118 D	12-08-1999
		DE 69603118 T	03-02-2000
		JP 8339637 A	24-12-1996
		JP 2839878 B	16-12-1998
		JP 10031876 A	03-02-1998
		JP 3062152 B	10-07-2000
		JP 11018054 A	22-01-1999
		JP 2857144 B	10-02-1999
		JP 11075158 A	16-03-1999
		JP 2857145 B	10-02-1999
		JP 11075159 A	16-03-1999
		JP 2857146 B	10-02-1999
		JP 11075160 A	16-03-1999
		KR 256663 B	15-05-2000
		KR 256517 B	15-05-2000
		KR 253614 B	01-05-2000
		KR 209847 B	15-07-1999
		US 6112009 A	29-08-2000
		US 6134383 A	17-10-2000
EP 0986062 A	15-03-2000	EP 0991072 A	05-04-2000
		AU 5742899 A	27-03-2000
		WO 0014744 A	16-03-2000
		AU 5854999 A	27-03-2000
		WO 0014743 A	16-03-2000
EP 1021048 A	19-07-2000	JP 2000268537 A	29-09-2000
EP 0986248 A	15-03-2000	AU 5854899 A	27-03-2000
		WO 0014952 A	16-03-2000
EP 0967603 A	29-12-1999	JP 2000011546 A	14-01-2000

**THIS PAGE BLANK (USPTO)**